



Wing II


1. Dimensions/Weight




WING II
weight: 5.70 kg




WING II CLICK
weight: 5.70 kg




WING II CFS
weight: 5.70 kg




Wing II CFL**
weight: 7.70 kg




WING II.20
weight: 5.70 kg




WING II.20 CLICK
weight: 5.70 kg




WING II W
weight: 6.60 kg



WING II TR
weight: 6.60 kg



WING II W CLICK-J4
weight: 7.00 kg



UNIVERSAL ROW CONNECTOR
weight: 0.95 kg

2. Materials/Versions

2.1. Frame

2.1.1. Frame

4-leg frame – made of $\varnothing 20 \times 2.0$ mm steel tube and $\varnothing 6$ mm steel bar.

CFS sled frame – made of $\varnothing 16 \times 2.0$ mm steel tube and $\varnothing 18 \times 1.5$, $\varnothing 5$ mm steel bar.

CFL cantilever frame – made of $\varnothing 22 \times 2.5$ mm steel tube and 25×4.0 mm flat bar.

Finish options

- chromium plated (CR),
- powder-coated in White aluminium RAL 9006 (ALU),
- Traffic white RAL 9016 (WT),
- powder-coated in Jet black RAL 9005 (BL),
- or „Fashion Collection“ colour.

Stacking:

4L – 8 pieces,

CFS, CFL – 10 pieces.

Wing cart and Universal chair cart available.

2.1.2. Click/link

CLICK – $\varnothing 6$ mm steel rod integrated with the frame to connect Wing II 4L into rows.

CLICK-J4 – $\varnothing 6$ mm steel rod integrated with the frame to connect Wing II 4L and WING II W 4L into rows.

UNIVERSAL ROW CONNECTOR

- dedicated to connect opposite rows of chairs,
- distance adjustment: 450–510 mm,
- possibility of mounting to the floor,
- powder-coated in Jet black RAL 9005 (BL).

2.2. Glides

Glides for soft floors (GB) as standard or hard floors (GBF) as an option.

2.3. Seat and backrest

Wooden shell (WOOD) – made of 8-layer beech plywood, thickness 10.5 mm.

Laminated wooden shell (LAMINATE) – made of 8-layer beech plywood, thickness 10.5 mm.

Visible plywood edges protected with wax.

Wooden shell with upholstered pad on seat (SEAT-PLUS) – the structure of seat pad is made of 3-layer beech plywood, thickness 4.5 mm, covered with foam thickness 15 mm, density 25 kg/m^3 .

Wooden shell with upholstered seat pad and backrest pad (PLUS) – seat and backrest pad structure made of 3-layer beech plywood, thickness 4.5 mm, covered with foam thickness 15 mm, density 25 kg/m^3 .

2.4. Armrests

Fixed armrest – integrated with chair frame (WING II W), armrest pads (50×180 mm) made of plywood, thickness 17 mm.

Finish options:

- stained (NF-xx),
- laminated.

2.5. Writing tablet

Writing tablet (right and left hand version) made of 8-layer beech plywood, thickness 10.5 mm. Tablet top dimensions: 355×283 mm.

Finish options:

- stained plywood,
- laminated plywood, visible plywood edges protected with wax.

3. Accessories

WING CART – made of steel tube diameter 25×2.0 mm with supports and diameter 20×2.0 mm for handles with rod bar diameter 8 mm, handles to be fixed to the cart after stacking the chairs, 4 castors diameter 75 mm, 2 castors with manual brakes, powder-coated in White aluminium RAL 9006 (ALU) or Jet black RAL 9005 (BL) colour. 24 pcs to be stacked back to back.

Cart dimensions:

$650 \text{ mm} \times 1720 \text{ mm} \times 840 \text{ mm}$ (height)

4. Packaging

4 pcs per box (assembled chair).

5. Technical regulations, approvals and quality marks for the chairs (for selected product configurations)

REMODEX – durability certificate: EN 16139, EN 1728, EN 1022

Proven Safety Certificate GS.